

SAKRETE® PRO TIPS: CHOOSE THE RIGHT MIX

Picking the perfect mix for a job isn't always easy.

We've got you covered with Pro Tips for choosing the right Sakrete product for every application.



THE ORIGINAL BAGGED CONCRETE MIX

APPLICATIONS	TIMING	SLUMP	PERFORMANCE
Small to medium new construction	Foot Traffic: 24 Hours	2-3"	2,500 psi in 7 days 4,000 psi in 28 days



REINFORCED WITH POLYPROPYLENE FIBERS TO MINIMIZE CRACKING

APPLICATIONS	TIMING	SLUMP	PERFORMANCE
Formulated to reduce surface cracks due to shrinkage	Foot Traffic: 24 Hours	2-3"	2,500 psi in 7 days 4,000 psi in 28 days



SETS FAST TO KEEP THE JOB ON TRACK

APPLICATIONS	TIMING	FEATURES	PERFORMANCE
Ideal for setting posts and poles	Set Time: 30 minutes Foot Traffic: 6 hours	No mixing required when used for post setting	3,500 psi in 7 days 4,000 psi in 28 days



FORMULATED WITH LIGHTWEIGHT AGGREGATES FOR 67% HIGHER YIELD

APPLICATIONS	TIMING	SLUMP	PERFORMANCE
Delivers 1 cu.yd. with 27 80# bags vs. 45 bags of standard mix	Foot Traffic: 24 Hours	3-4"	4,000 psi in 7 days 5,500 psi in 28 days



DELIVERS HIGH EARLY STRENGTH, ESPECIALLY IN COLD WEATHER

APPLICATIONS	TIMING	SLUMP	PERFORMANCE
Suitable for pouring concrete countertops as thin as 1.5"	Foot Traffic: 12 Hours	2-3"	3,500 psi in 7 days 5,000 psi in 28 days



A VERSATILE, HIGH-STRENGTH MIX PERFECT FOR REPAIRS.

APPLICATIONS	TIMING	FEATURES	PERFORMANCE
Wide crack repairs or overlays up to 2" deep	Foot Traffic: 24 Hours	Suitable replacement for floor mud when laying tile, creating shower pans and more	3,000 psi in 7 days 5,000 psi in 28 days