3" Split Limestone



Installation Specifications At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to 3" Split Limestone

Standard Colors:	Cream, Genoa Sands, Oak, Walnut or Any Custom Color
Grout Joint Width:	Drystacked
Grouting Options:	Drystacked
Grout Joint Color:	Color should be added to mortar to complement stone color.
Accessories:	Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern:	Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. See catalog photos for recommended installation pattern.	
Chalk Lines:	Should be used by installer to ensure a straight and level pattern.	
Sealing:	Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.	
Freeze-Thaw:	When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.	
Drystacked:	A polymer modified mortar should be used for all drystacked applications.	
Installation Info:	Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.	
Profile Properties		

L

Size:	3" in height and in the following lengths: 6", 10", 12", 14" and 18".
Thickness:	1" - 1¾"
Weight:	7 to 10 lbs. per square foot.
Packaging:	Available in big boxes (120 sq ft Flats & 100 lft Corners) or Dura-Paks (12.5 sq ft Flats & 12.5 lft Corners).
	When purchasing 3" Split Limestone, coverage is based on installation with tightly fitted joints.

Drystacked



3" Split Limestone

COLOR: GENOA SANDS

Drystacked



3" Split Limestone

COLOR: WALNUT